



We hope you are happy with the installation of new door(s) at your home by the association.

Your Main Entrance/ Front Door is a Composite Door.

This leaflet will outline the best way to care for this product to ensure it stays in good condition for a long time.

What is a Composite Door?

Composite doors are made up of multiple materials such as PVC, wood, insulating foam and plastic. The combination of materials result in a door that is strong, durable and secure as well as being more efficient than uPVC at keeping heat from escaping.



How to care for your Composite Door:

Due to their design composite doors need very little maintenance to keep them in good condition, you don't need any special cleaning fluid or any specialist equipment to keep them looking new



Cleaning: Once a month clean the door and door frame using a soft cloth and warm, soapy water to remove grit and grime, especially in areas surrounding the hinges and the lock and handle where build up of dirt can cause problems with the opening and closing of your door.


If your door has a glass panel, clean away dirt and grime with warm water and a soft cloth. For optional shine you can use a glass cleaner after washing with water.

Maintenance: Once every six months, we request if you can please add a little lubricating oil such as WD40 to the hinges to keep them moving freely when opening and closing.



PLEASE DO NOT SAND, PAINT OR VARNISH YOUR DOOR AS THIS WILL DAMAGE IT

DO NOT INSTALL A CATFLAP AS YOU MAY INCURE A CHARGEABLE COST





We hope you are happy with the installation of new door(s) at your home by the association.

Your Rear or Side Entrance Door is a uPVC Door.



This leaflet will outline the best way to care for this product to ensure it stays in good condition for a long time.

What is a uPVC Door?

uPVC is a common, strong but lightweight plastic used in construction. uPVC doors are low maintenance and require no painting or staining.

How to care for your uPVC Door

Cleaning: Once a month clean the door and door frame using a soft cloth and warm, soapy water to remove grit and grime, especially in areas surrounding the hinges and the lock and handle where build up of dirt can cause problems with the opening and closing of your door. If your door has a glass panel, clean away dirt and grime with warm water and a soft cloth. For optional shine you can use a glass cleaner after washing with water. **Do not use** abrasive cleaner or wire wool as this will damage the surface of uPVC



Maintenance: Once every six months we request if you can please lubricate all moving parts. Stainless steel hinges should be oiled at the rivet points with light silicone lubricant. Other metal components should be coated with petroleum jelly. **Do not use** spray oil or excessive lubrication.

Make sure windows and doors are fully closed before operating handles. This will avoid straining the lock mechanism.

Do not force the handles or locks. If they will not operate, check there are no obstructions and try again



PLEASE DO NOT SAND, PAINT OR VARNISH YOUR DOOR AS THIS WILL DAMAGE IT

DO NOT INSTALL A CATFLAP AS YOU MAY INCURE A CHARGABLE COST





We hope you are happy with the installation of new door(s) at your home by the association.

Your French Door (open out) is a uPVC Door.

This leaflet will outline the best way to care for this product to ensure it stays in good condition for a long time.



What is a uPVC Door?

uPVC is a common, strong but lightweight plastic used in construction. uPVC doors are low maintenance and require no painting or staining.

How to care for your uPVC Door

Cleaning: Once a month clean the door and door frame using a soft cloth and warm, soapy water to remove grit and grime, especially in areas surrounding the hinges and the lock and handle where build up of dirt can cause problems with the opening and closing of your door.



If your door has a glass panel, clean away dirt and grime with warm water and a soft cloth. For optional shine you can use a glass cleaner after washing with water. **Do not use** abrasive cleaner or wire wool as this will damage the surface of uPVC

Maintenance: Once every six months we request if you can please lubricate all moving parts. Stainless steel hinges should be oiled at the rivet points with light silicone lubricant. Other metal components should be coated with petroleum jelly. **Do not use** spray oil or excessive lubrication.

Make sure windows and doors are fully closed before operating handles. This will avoid straining the lock mechanism.

Do not force the handles or locks. If they will not operate, check there are no obstructions and try again



PLEASE DO NOT SAND, PAINT OR VARNISH YOUR DOOR AS THIS WILL DAMAGE IT

DO NOT INSTALL A CATFLAP AS YOU MAY INCURE A CHARGEABLE COST

